





Stacked Ledgestone Collection







## Installation Method

Step 1:



Step 2:



Step 3:




Step 4:





### imestone Collection







C - Corner Available

### Corner Treatment

CraftStone® veneers come with 90° outside corner components that offer full-thickness apperance.





# **Technical Specification**

CraftStone® products carry a 25-year limted warranty when used on structures that conform to local building codes and installed according to the maunfacturer's instruction. Warranty is limited to replacement of defective materials only. Damages resulting from building settlement, wall movement, force contact, contact with chemicals or paint, discoloration due to airborne contamination, staining or oxidation, will not be covered under the warranty. Warranty is non-transferable and is only limited to the original purchaser.

### Non-Combustible

CraftStone® products show zero flame spread and zero smoke development.

### **General Properties**

Material Composition: Portland Cement, Light-Weight Aggregates and Iron Oxide Pigments.

Unit Weight: 30~40kg/m<sup>2</sup> (varies according to profile)

Thickness: 15~60mm (varies according to profile)
Water Absorption: <13%
Open Porosity\*: <35%
Compressive Strength\*: >12.0N/mm²
Flexural Strength\*: >5.0N/mm²





# CraftSeal Nano Technology

### Water Repellent

CraftStone® products feature the addition of water-based CraftSeal that greatly enhances the stone's performance in humid condition.

CraftSeal is apply onto all our products before packaging to provide the maximum water repellent effect.

Contact us for more information on CraftSeal!

